

## TANK SPRAYER 200L

Portable industrial spray applicator units for applying pre-mixed chemical solutions.



### OVERVIEW

- PRODUCT CODE : **TSA200**
- CAPACITIES : **200 L**
- POWER SUPPLY : **Air pressure**
- AIR PRESSURE REQUIREMENTS : **3- 6 bar with 145 to 285 l/min**
- DISCHARGE HOSE LENGTH : **5/10/15/20/25 m**
- LANCE LENGTH : **75 cm or Telescopic 300 cm (2 x 150 cm)**
- LIQUID TEMPERATURE : **Min 5°C, max 40°C**
- SPRAY OUTPUT : **3 - 6 liters/minutes**
- PUMP SEALS : **Santoprene, Viton**
- ALLOWED FLUIDS : **SANTOPRENE - Acids Alkaline, Soaps, Alcohol, Ketones, Potable Water; VITON - Oils, Solvents, D-Limonene, Aromatic & Halogenated Hydrocarbons, Acids**
- WHEEL TYPE : **Non-marking wheels or Food approved poliamid**
- WEIGHT : **29 kg**

### Pallet Load

- PACKAGE SIZE: **570 x 840 x 770 mm**
- PALLET: **1200 x 1000mm**
- N PACKAGES: **4**
- N LAYERS: **2**
- SURFACE USAGE: **79.8%**
- VOLUME USAGE: **72.3%**
- TOTAL WEIGHT: **60 KG**

